

IMPACT 90

Mobile lifter for intensive use.

For live applications:

www.youtube.com/HOVMANDIMPACT



Mobile, easy to manoeuvre and extremely space-saving.




Designed for maximum daily use. The Impact 90 is not only the fastest lifter in this product range, but also one of the most resilient. It effortlessly moves, lifts and transports objects with a total weight of up to 90 kg. It also features overload protection, a safety clutch, shielding for all moving parts and a battery indicator. The three different mast heights can be combined with four different leg sets. These also include adjustable legs with internal widths of 450–610 mm or 650–810 mm (Flex 1 and Flex 2). In addition, an extensive range of lifting equipment is available for a wide variety of applications.

TECHNICAL SPECIFICATIONS:


Lift column type	Lifting capacity kg	Stroke length mm	Overall height mm	Lifting speed mm/sec	Battery voltage V/Ah	Total weight kg
90 L	90	1242	1520	200/100	24/9	43*
90 M	90	1642	1920	200/100	24/9	45*
90 H	90	2042	2320	200/100	24/9	47*

* varies depending on chassis and lifting equipment


LIFTING TOOLS FOR CRATES AND BOXES



WOODEN PLATFORM




WOODEN PLATFORM WITH ROLLERS



ALUMINIUM PLATFORM




PEHD PLATFORM




PEHD PLATFORM WITH ROLLERS




STAINLESS STEEL PLATFORM




FORK



KLT FORK




TURNING FORK



FLEX FORK


LIFTING TOOLS FOR REELS




BOOM




DOUBLE BOOM




FLEX DOUBLE BOOM




BOOM + V-BLOCK




PLATFORM WITH EPV V-BLOCK




WAVE



MANUAL REEL
MANIPULATOR MRP1



MANUAL REEL
MANIPULATOR MRP2



MANUAL REEL
MANIPULATOR MRP3

LIFTING TOOLS FÜR BUCKETS AND JERRYCANS



CANISTER TIPPER LARGE




CRANE ARM




CRANE ARM TRAVERSE WITH
STRAPS

LEG SETS



STANDARD
Rear wheel with brake
Leg length: 500 mm



CENTER
Suitable for Euro pallets.
Rear wheel with brake



FLEX 1
Adjustable width of
450-610 mm



FLEX 2
Adjustable width of
650-810 mm